

COMPETITIVE COMPARISON

| MODEL | | Kubota SVL95-2s | Bobcat T770 | CAT 299DXHP | Takeuchi TL12 | Deere 333E | CASE TV380 | |
|--|--|-----------------|--------------|--------------|---------------|--------------|--------------|-------------|
| Lift | Lift Arm Path | Vertical | Vertical | Vertical | Radial | Vertical | Vertical | |
| | Emission Level | Tier 4 Final | Tier 4 Final | InterimTier4 | InterimTier4 | InterimTier4 | Tier 4 Final | |
| Engine | Engine Model | V3800-TIEF4 | D34 | Cat C3.8 DIT | V3800-CR-TE4 | 4TNV94CHT | F5BFL413E | |
| | Manufacture | Kubota | Doosan | Cat | Kubota | Yanmar | FPT | |
| | Horsepower | hp | 96.4 | 92 | 106 | 108 | 97 | 90 |
| | Peak torque | Nm | 347 | np | np | 375 | 395 | 383 |
| | Rated RPM | rpm | 2400 | 2400 | np | 2400 | 2500 | 2500 |
| | Cylinders | each | 4 | 4 | 4 | 4 | 4 | 4 |
| | Displacement | L | 3.769 | 3.4 | 3.8 | 3.769 | 3.1 | 3.4 |
| | Bore Stroke | mm | 100x120 | np | 100 x 120 | 100 x 120 | np | 99x110 |
| | Hand or Dial / Foot Throttle | type | Dial/Foot | Hand | Hand/Foot | Hand | Hand | Dial/Foot |
| | Rated Operating Capacities: 50% Tipping Load | lb | 4572 | 4965 | 4650 | 4051 | 4725 | 3800 |
| Rated Operating Capacities: 35% Tipping Load | lb | 3200 | 3475 | 3225 | 2833 | 3300 | 2660 | |
| Tipping Load ISO 14397 | lb | 9143 | 9929 | 9300 | 8102 | 9425 | 7600 | |
| Breakout Force, Tilt Cylinder | lb | 7961 | 5659 | 7552 | 8670 | 13875 | 7510 | |
| Breakout Force, Lift Arm Cylinder | lb | 6742 | np | 6111 | 8550 | 6600 | 6020 | |
| Traction Force | kgf | 5524 | np | 4280 | 6244 | 5227 | np | |
| Undercarriage | Track Width - Standard | in (mm) | 17.7 (450) | 17.7 (450) | 17.7 (450) | 17.7 (450) | 17.7 (450) | |
| | Track Width - Optional | in (mm) | n/a | 12.6 (320) | - | - | 15.6 (400) | n/a |
| | Length of Track on ground | in (mm) | 65.6 (1667) | 63.7 (1618) | 69.6 (1767) | 62.8 (1595) | np | 64.5 (1638) |
| | Track Gauge | in (mm) | 59.5 (1512) | 60.3 (1532) | np | np | np | 58.3 (1481) |
| | Track Rollers (per side) | each | 5 | 5 | 5 | 6 | 5 | 4 |
| | Independent Bogie Carriage | | NA | NA | NA | NA | NA | NA |
| | Travel Speed Lo | mph | 5 | 6.6 | 5.2 | 4.9 | 5.3 | 8.2 |
| | Travel Speed Hi | mph | 7.3 Std | 10.7 Opt | 8.4 Std | 7.2 Std | 7.8 Std | 12.2 |
| | Ground Pressure | psi | 4.4 | 4.2 | 5.3 | 4.6 | 4.5 | 4.5 |

COMPETITIVE COMPARISON

| MODEL | | Kubota SVL95-2s | Bobcat T770 | CAT 299DXHP | Takeuchi TL12 | Deere 333E | CASE TV380 |
|----------------------------|---|-----------------|--------------|--------------|---------------|-------------|--------------|
| Hydraulics | Hydraulics self-leveling bucket | Std | Opt | Opt | Std | Opt | Opt |
| | Loader Hydraulic Flow GPM (L/min) | 24.1 (91.0) | 23 (87.1) | 23 (87.1) | 23.2 (88) | 25 (95) | 24.2 (91.5) |
| | Loader Hydraulic Pressure psi | 3495 | 3495 | 3335 | 3045 | 3452 | 3050 |
| | Auxiliary Hydraulic Flow Std/HF (Opt) GPM (L/min) | 40 (151) | 36.5 (138) | 40 (151) | 40.4 (153) | 34.1 (129) | 37.6 (142.5) |
| | Auxiliary Hydraulic Pressure PSI | 3553 | 3495 | 4061 | 3045 | 3452 | 3050 |
| Dimensions and Capacities | Length w/o Bucket in (mm) | 123.5 (3137) | 114.3 (2903) | 123.5 (3137) | 123.5 (3135) | 120 (3050) | 119.1 (3025) |
| | Length w/Bucket on ground in (mm) | 154.6 (3929) | 141.6 (3597) | 151.8(3856) | np | 144 (3660) | 143.2 (3639) |
| | Height to Top of Cab in (mm) | 83.3 (2116) | 81.3 (2065) | 83.7 (2126) | 91.3 (2320) | 84.6 (2150) | 80.4 (2042) |
| | Vehicle Width in (mm) | 77.2 (1962) | 78.0 (1981) | 78.0 (1981) | 73.2 (1860) | 80.7 (2050) | 76 (1930) |
| | Ground Clearance in (mm) | 11.5 (293) | 8.1 (206) | 9.1 (231) | 13.5 (344) | 10.2 (260) | 9.5 (241) |
| | Departure Angle degrees | 31 | 31 | 30 | 30 | 31 | 32 |
| | Hinge Pin Height at max lift in | 128.5 | 132 | 125.6 | 126.1 | 126 | 131.6 |
| | Reach at max lift and dump in | 40.7 | 33.6 | 30.6 | 38.8 | 32.3 | 31.4 |
| | Clearance at max lift and dump in | 97.3 | 104.3 | 94.3 | 95.7 | 102 | 105.1 |
| | Maximum Dump Angle degrees | 43 | 42 | 52 | 38.7 | 45 | 53.5 |
| | Maximum Rollback Angle on Ground degrees | 27 | 31 | np | 31.4 | 35 | 34.2 |
| | Hydraulic System gal | 18 | np | 14.5 | 25 | np | 11.8 |
| | Hydraulic Tank gal | 10 | np | 10.3 | 15.8 | np | 6 |
| | Fuel Tank gal | 28.8 | 27.2 | 32.2 | 23.8 | 25.5 | 25.5 |
| | Diesel Exhaust Fluid (DEF) gal | 5 | np | NA | NA | NA | 2.8 |
| Operating Weight (ROPS) lb | 11299 | 10465 | 11612 | 11618 | 11800 | 10550 | |

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.