

RTV400Ci/RTV500 Kubota

SPECIFICATIONS

Specifications

Model			RTV400Ci	RTV500
	Туре		1-cylinder, GAS, OHC, Air-cooled, EFI	2-cylinder, GAS, OHC, Water-cooled, EFI
Engine	Displacement	cu. in. (cc)	24.6 (404)	27.8 (456)
	Horsepower H	IP (kW)/rpm	16.0 (11.9) / 4800	15.8 (11.8) / 3600
Fuel tank capacity U.S. gals (ℓ)		5.2 (20)		
Transmission		CVT PLUS Continuously Variable Transmission (CVT) with Inertial Clutch	VHT PLUS Variable Hydro Transmission	
Max. Traveling speed mph (km/h)			25 (40)	
Wheels, drive system			4, 4WD w/2WD selection	
Differential lock		Standard; hand operated with mechanical holder		
Gear selection		Hi-Lo range forward, neutral, reverse		
Front / Rear		Dry-disc brakes		
Brakes	Parking brake		Rear wheel, hand lever	
Steering		Rack & Pinion		
Suspension	Front / Rear		Independent, Mac-Pherson strut-type / Semi-independent, Multi-link	
Dimensions	Length	in. (mm)	105.9 (2690)	
	Width	in. (mm)	54.7 (1390)	
	Height, overall	in. (mm)	72 (1829)	
	Front tread centers	in. (mm)	40 (1016)	
	Rear tread centers	in. (mm)	41 (1041)	
	Wheelbase	in. (mm)	70.9 (1800)	
	Ground clearance front/rear axle	in. (mm)	8.1 (205) / 6.9 (175)	
	Turning diameter	ft. (m)	22.9 (7)	
Max. rolling weight (Towing capacity) lbs. (kg)		1102 (500)		
Payload capacity lbs. (kg)		1058 (480)	949 (430)	
Weight lbs. (kg)		1246 (565) with ATV Tires, 1257 (570) with HDWS Tires	1358 (615) with ATV tires, 1369 (620) with HDWS tire	
Cargo bed	$Width \times Length \times Depth$	in. (mm)	40.6 (1032) × 33.7 (856) × 11.4 (290)	
	Volume	cu. ft. (m³)	9.0 (0.25)	
	Bed height (unloaded)	in. (mm)	31.9 (810)	
	Cargo bed load	lbs. (kg)	441 (200)	
Tires	Front		24 × 9-12 ATV, 6PLY	
			24 × 9-12 HDWS, 6PLY	
	Rear		24×11-12 ATV, 6PLY	
			24×11-12 HDWS, 6PLY	
Body color			Orange, Camouflage (Realtree® Hardwoods®)	
Speedometer			Opt.	
Front guard			Opt.	
Headrest			Opt.	

*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd.

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this web site are shown with optional accessories. For off-highway use only.