

Kubota®

RTV500 Utility Vehicles

Competitive Comparison				
MODEL		Kubota RTV500	John Deere Gator TX 4x2	Kawasaki Mule 610 4x4
Engine	Make	Kubota GZ460-E-UV	Kawasaki	Kawasaki
	Type	4-cycle gas	4-cycle gas	4-cycle gas
	Cylinders	2	1	1
	Cooling	Liquid-cooled	Air-cooled	Air-cooled
	Valving	Overhead Cam	Overhead Valve	Overhead Valve
	Fuel Delivery	Electronic Fuel Injection (EFI)	Carburetor	Carburetor
	Displacement	27.8 (456)	25.4 (401)	25.4 (401)
	Horsepower	15.8 (11.8)	13 (9.7)	N/P
Exhaust system		Muffler with spark arrestor	Muffler with spark arrestor	Muffler with spark arrestor
Fuel tank capacity		5 (19)	5 (18.9)	4.1 (15.5)
Transmission		Variable hydro transmission (VHT)	Belted CVT	Belted CVT
Max. Traveling speed		25 (40)	20 (32)	25 (40)
Wheels, drive system		2WD/4WD selectable	2WD	2WD/4WD selectable
Gear selection		Hi-Lo range forward, neutral, reverse	forward, neutral, reverse	Hi-Lo range forward, neutral, reverse
Brakes		disc/disc	disc/disc	drum/drum
Steering		Rack & Pinion	Rack & Pinion	Rack & Pinion
Suspension	Front	Independent, Mac-Pherson strut	Independent spring over strut	Independent, Mac-Pherson strut
	Rear	Semi-independent, Mult-link	Single parabolic leaf spring	Swing axle
Dimensions	Length (without front guard)	105.9 (2690)	105.6 (2681)	107.1 (2720)
	Width	54.7 (1390)	60 (1525)	52.6 (1336)
	Height, overall	72 (1829)	43.6 (1108)	70.9 (1801)
	Front tread centers	40 (1016)	50 (1270)	N/P
	Rear tread centers	41 (1041)	48 (1219)	N/P
	Wheelbase	70.9 (1800)	72.5 (1841)	70 (1778)
	Ground clearance front/rear axle	8.1 (206) / 6.8 (172)	N/P	N/P
	Turning radius	11 (3353)	N/P	10.8 (3292)
Max. rolling weight (Towing capacity)		1,102 (500)	1,000 (454)	1,100 (499)
Payload capacity		1,014 (460)	1,000 (454)	926 (420)
Weight		1,278 (580)	1,032 (468)	1,010 (468) dry
Cargo bed	Cargo box material	Steel	Steel	Steel
	Width x Length x Depth	40.6 (1032) X 33.7 (856) X 11.4	49 (1245) X 43.9 (1115) X 9	35.4 (899) X 41.1 (1044) X 9.6 (244)
	Volume	9.0 (0.25)	11.2 (0.32)	10.9 (0.31)
	Cargo bed load	441 (200)	600 (272)	400 (181)
Operator & Occupant	Seating	2	2	2
	Rollover Protection System	OSHA 1928/SAE J1194	N/A	SAE J1194
	Sound level, operator's ear	83	N/P	N/P
Tires	Front	24 x 9-12 ATV, 6PLY	22 x 9.5-10	24 x 9-10
		24 x 9-12 HDWS, 6PLY	N/P	N/P
	Rear	24 x 11-12 ATV, 6PLY	24 x 10.5-10	24 x 11-10
		24 x 11-12 HDWS, 6PLY	24 x 12-10	N/P
Body color		Orange, Realtree Hardwoods Camo	Green	Green, Red

N/A = Not Available N/P = Not Published

These comparisons of specifications are based on the latest data available to Kubota at the time of publication. Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.