

NEW! BOOMER™ COMPACT TRACTOR 24 HP

BOOMER 24



YOUR JOBS — NOW MADE EASIER

This new Boomer™ 24 compact tractor is the ultimate power tool for homeowners, rural lifestyles, landscapers and hobby farmers. Responsive, efficient and comfortable, they're built to make your jobs easier.

THE POWER YOU NEED

Quiet, fuel-efficient Tier IV 3-cylinder engines give you the power you need for loading, mowing, digging, blowing snow, tilling and much more. You get fast implement and steering response thanks to the high-capacity hydraulic system.

OPERATING EASE

The word "easy" defines Boomer tractors. Controls come easily to hand, the seat and steering wheel adjust to match every operator, and the large, uncluttered operating platform gives you plenty of legroom to stretch out. Controls are color-coded and clearly marked so you are confident of your every move.

SMOOTH SPEED CHANGES

The Boomer 24 is equipped with a 2-range hydrostatic transmission. It makes direction changes even easier with a new dual pedal design. Push one pedal to go forward, push the second pedal to go backward. No clutching or hand shifting is required. You also get the convenience of cruise control as a standard feature.

PROVEN MANEUVERABILITY AND TRACTION

Your Boomer tractor is designed to get you in and out of tight spots and maneuver easily around and — thanks to generous ground clearance — over obstacles. Four-wheel drive gives you the traction you need to get through rough patches. When the going gets tough, simply step on the differential lock foot pedal and both rear wheels lock together for added traction to get through snow, mud or rough, slippery ground.

SIMPLE SERVICE

Boomer tractors are a snap to maintain. Checkpoints are easy to reach and the flip-up hood gives you complete access to the engine, battery, radiator and air filters.

BOOMER™ 24 COMPACT TRACTOR SPECIFICATIONS

BOOMER 24

ENGINE	
Gross horsepower, hp (kw)	24.4 (18.2)
Rated speed (rpm)	2700
Type	3-cylinder diesel Tier IV
Displacement, cu. in. (L)	80.4 (1.3)
Air cleaner	Single replaceable dry element
Fuel tank, gal. (L)	6.6 (25)
Alternator, amps	50
PTO	
PTO HP (HST), hp (kw)	Standard rear and mid PTO 16.7 (12.4)
PTO speed (rpm)	540 rear/2000 mid PTO
PTO type	Electro-hydraulic engaged; independent
TRANSMISSION	
Type, Mechanical/hydrostatic	HST+2 range
Maximum forward speed, HST – mph (kph), R4	11.3 (18.6)
Cruise control	Standard
Rear diff. lock engagement	Mechanical/foot
Brake type	Mechanical/wet, multi disc
HYDRAULICS	
Implement hydraulic flow, gal. (lpm)	6.7 (25.5)
Steering hydraulic flow, gal. (lpm)	2.9 (11)
Remote valve	Optional DIA
3-point lift capacity @ ball ends, gal. (lpm)	1433 (650)
3-point linkage category	1
Steering type	Hydrostatic
DIMENSIONS (w/R4 tires)	
Wheel base, in. (cm)	59 (150)
Length, in. (cm)	103.6 (263.2)
Height (ROPS), in. (cm)	85.5 (217.3)
Width, in. (cm)	49.1 (124.7)
Weight (HST), lbs. (kg)	1708 (775)
Tire choice	R3 turf tread or R4 industrial tread



We've got your back with the FREE Boomer Guard 5 Limited Warranty. It provides 5 years of worry-free operation, including 2 years of bumper-to-bumper coverage plus an extra 3 years of powertrain protection. You won't find a better compact tractor or warranty anywhere.

READY FOR ANY JOB

Whether you need to load mulch, mow the lawn, clear a pasture, dig a trench, till the garden, move snow, clean stalls or install a fence, Boomer tractors are for you. These tractors make it easy to change implements so you can move quickly from job to job.

- Category I three-point hitch
- One optional rear hydraulic remote
- Independent, electro-hydraulic 540-rpm rear PTO
- Standard electro-hydraulic independent mid-PTO to power mid- and front-mount implements
- Many accessories, implements and attachments to match your needs

FRONT LOADER MODEL

235TL

Lift capacity @ max. height @ pins, lbs. (kg)	1034 (470)
Breakout force @ pins, lbs. (kg)	1672 (760)
Maximum lift height @ bucket pivot pin, in. (cm)	80.7 (205)
Maximum dump angle – degrees	51°
Bucket rollback angle – degrees	29°

NOTES: Specifications based on ASAE (S301.3) and are subject to change without notice. Dimensional and performance specifications are based on typical tractors and tire sizes.



Open, spacious operator's platform gives you lots of legroom.



Rear PTO and 3-point hitch allow you to attach countless implements to any job.



Learn more at www.newholland.com/na



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2014 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.