

**B****B-Series****Kubota****SPECIFICATIONS****Specifications**

Model		B2320	B2620	B2920
<b>Engine</b>				
Type		E-TVCS, liquid cooled, 3-cylinder diesel		
Make, Model		Kubota D1005	Kubota D1105	Kubota D1305
PTO horsepower	HP (kW)	DT:18.0 (13.4)/HSD:17.0 (12.7)	19.0 (14.2)	21.0 (15.7)
Engine gross horsepower	HP (kW)	23.0 (17.2)	26.0 (19.4)	29.0 (21.6)
Rated RPM	rpm	2800		
Bore and stroke	in. (mm)	3.0 × 2.9 (76 × 73.6)	3.1 × 3.1 (78 × 78.4)	3.1 × 3.5 (78 × 88)
Displacement	cu. in. (cc)	61.1 (1001)	68.5 (1123)	77.0 (1261)
Air cleaner		Dual paper element		
Lubrication		Forced lubrication		
Cooling system		Pressurized radiator		
Radiator fan		Radial air flow		
<b>Capacities</b>				
Fuel tank	gal (ℓ)	6.9 (26)		
Cooling system	qts. (ℓ)	4.1 (3.9)		
Engine oil	qts. (ℓ)	3.3 (3.1)		3.7 (3.5)
Transmission case	gal (ℓ)	DT:3.7 (14)/HSD:4.0 (15)	4.0 (15)	
<b>Drive train</b>				
Clutch		Dry single plate		
Transmission		Gear (9 Forward, 3 Reverse) / HST (3 range)	HST (3 range)	
Differential lock		Standard		
Final drive		Spur gear		
Brake		Wet disc type		
PTO	rpm	DT: Transmission driven with one way clutch / HSD: Live		Live
	Rear	rpm		
	Mid	rpm		
<b>Hydraulics</b>				
Type		Open Center, Gear Pump		
Pump		Dual Pump, 3P: 4.7 (17.9) Power Steering: 3.6 (13.5)		
Total pump output	gpm (ℓ/min.)	8.3 (31.4)		
Hydraulic outlet		Front outlet (w/ standard valve)		
3-point hitch		Category I		
Hydraulic control system		Quarter inching valve		
Lift capacity at lift point	lbs. (kg)	1356 (615)		
	24" behind LP	lbs. (kg)		
		1058 (480)		
Steering		Integral type power steering		
<b>Standard tire size</b>				
	Front	6-12		7-12
	Rear	9.5-16		11.2-16
<b>Traveling speeds (at rated engine rpm)</b>				
	Forward	mph (km/h) DT 9th:11.2(18)/HSD:0-11.7(0-18.9)		0-12.6 (0-20.2)
	Reverse	mph (km/h) DT 3rd:5.4(8.7)/HSD:0-9.4(0-15.1)		0-10.0 (0-16.1)
<b>Dimensions</b>				
Overall length (w/o 3-point hitch)	in. (mm)	93.9 (2385)		95.1 (2415)
Overall width (min. tread)	in. (mm)	45.1 (1145)		49 (1245)
Wheelbase	in. (mm)	61.5 (1563)		
Ground clearance	in. (mm)	12.0 (305)		12.8 (325)
Tread		Front: in.(mm) 31.5(800) Rear: in.(mm) 35.5(900)		Front: in.(mm) 32.1(815) Rear: in.(mm) 37.4(950)
Turning radius with brake	feet (m)	6.9 (2.1)		
Weight	lbs. (kg)	DT:1433 (650)/HSD:1477 (670)	1554 (705)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

**B****B-Series****Kubota****SPECIFICATIONS****Specifications**

Model	B2320DTN-1		B2320HSDN	
<b>Engine</b>				
Type	E-TVCS, liquid cooled, 3-cylinder diesel			
Make, Model	Kubota D1005-E3-D22			
PTO horsepower	HP (kW)	18.0 (13.4)		17.0 (12.7)
Engine gross horsepower	HP (kW)	23.0 (17.2)		
Rated RPM	rpm	2800		
Bore and stroke	in. (mm)	3.0 × 2.9 (76 × 73.6)		
Displacement	cu. in. (cc)	61.1 (1001)		
Air cleaner		Dual paper element		
Lubrication		Forced lubrication		
Cooling system		Pressurized radiator		
Radiator fan		Radial air flow		
<b>Capacities</b>				
Fuel tank	gal (ℓ)	6.9 (26)		
Cooling system	qts. (ℓ)	4.1 (3.9)		
Engine oil	qts. (ℓ)	3.3 (3.1)		
Transmission case	gal (ℓ)	3.7 (14)		4.0 (15)
<b>Drive train</b>				
Clutch		Dry single plate		
Transmission		Gear shift (9 Forward, 3 Reverse)		HST (3 range)
Differential lock		Standard		
Final drive		Spur gear		
Brake		Wet disc type		
<b>PTO</b>				
Type		Transmission driven with one-way clutch		Live
Rear	rpm	540, 960		
Mid	rpm	N/A		2500
<b>Hydraulics</b>				
Type		Open Center, Gear Pump		
Pump		Dual Pump, 3-point hitch: 4.7 (17.9) Power Steering: 3.6 (13.5)		
Total pump output	gpm (ℓ/min.)	8.3 (31.4)		
3-point hitch		Category I		
Hydraulic control system		Position control valve		
Lift capacity at lift point	lbs. (kg)	1655 (750)		
24" behind LP	lbs. (kg)	1300 (590)		
Steering		Integral type power steering		
<b>Standard tire size</b>				
Front		5-12 R1/6-12R1		
Rear		8-16 R1/8.3-16R1		
<b>Tire size (standard/optional)</b>				
Forward	mph (km/h)	9th: 10.4 (16.8)		0-11.0 (0-17.7)
Reverse	mph (km/h)	3rd: 5.0 (8.1)		0-8.8 (0-14.2)
<b>Dimensions</b>				
Overall length (w/o 3-point hitch)	in. (mm)	92.9 (2360)		
Overall width (min. tread)	in. (mm)	35.4 (900)		36.9 (938)
Wheelbase	in. (mm)	61.5 (1563)		
Ground clearance	in. (mm)	11.8 (300)		
Tread Front		27.8 (705)		30.7 (780)
Rear		27.6 (700) to 29.5 (750)		
Turning radius with brake	feet (m)	6.9 (2.1)		
Weight	lbs. (kg)	1334 (605)		1390 (630)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

# B

# B-Series

# SPECIFICATIONS

## Implements Specifications

### FRONT LOADER

Model		LA304 (B2320)	LA364 (B2620/B2920)
Maximum lift height (to bucket pivot pin)	in. (mm)	74.0 (1880)	78.6 (1995)
Clearance w/ attachment dump	in. (mm)	56.2 (1428)	60.9 (1548)
Reach at maximum height (ROPS/CAB)	in. (mm)	23.5 (598)	22.7 (576)
Maximum dump angle	degrees	45	40
Attachment rollback angle	degrees	25	25
Digging depth at bucket leveled	in. (mm)	3.9 (100)	3.9 (100)
Overall height in carry position	in. (mm)	42.9 (1090)	43.4 (1102)
Material bucket width	in. (mm)	48 (1219)	50 (1270)
Lift capacity (pivot pin)	lbs. (kg)	772 (350)	952 (432)
Lift capacity (19.7 in. forward)	lbs. (kg)	545 (247)	661 (300)
Breakout force (19.7 in. forward)	lbf. (N)	1172 (5212)	1520 (6761)
Breakout force (pivot pin)	lbf. (N)	1648 (7330)	2144 (9536)
Raising time to full height w/o load	sec.	2.8	3.7
Lowering time w/o load (powerdown)	sec.	2.0	2.7
Attachment rollback time	sec.	1.9	2.6
Attachment dumping time	sec.	1.5	1.9
Rated flow	GPM (ℓ/min.)	4.4 (16.6)	4.7 (17.9)
Rated pressure	psi	2000	2000
Boom cylinder size (Bore × Stroke)	in. (mm)	1.57 × 13.2 (40 × 336)	1.77 × 13.7 (45 × 349)
Bucket cylinder size (Bore × Stroke)	in. (mm)	1.57 × 13.2 (40 × 336)	1.77 × 13.2 (45 × 336)
Bucket roll breakout force at ground line	lbf. (N)	1222 (5434)	1741 (7744)

### BACKHOE

Model		BH65
Bucket cylinder digging force	lbf. (N)	2585 (11500)
Dipperstick cylinder digging force	lbf. (N)	1687 (7500)
Transport height	in. (mm)	72.8 (1850)
Stabilizer spread transport	in. (mm)	50.4 (1280)
Ground clearance	in. (mm)	11.6 (294)
Overall width	in. (mm)	49.6 (1260)
Maximum digging depth	in. (mm)	80.1 (2034)
Digging depth, 2ft. flat bottom	in. (mm)	78.8 (2001)
Digging depth, 8ft. flat bottom	in. (mm)	56.4 (1432)
Operating height, fully raised	in. (mm)	105.4 (2677)
Loading height	in. (mm)	64.5 (1637)
Loading reach	in. (mm)	39.7 (1009)
Reach from swing pivot	in. (mm)	108.9 (2767)
Swing pivot to rear axle center line	in. (mm)	31.4 (797)
Bucket rotation	deg.	171
Stabilizer spread operating	in. (mm)	73.0 (1854)
Angle of departure per SAE J 1234	deg.	19
Leveling angle	deg.	11.8
Swing arc	deg.	150

### MID-MOUNT MOWER

Model		RCK54-29B	RCK60-29B
Type		Side discharge	
Number of blades		3	
Blade length	in. (mm)	18.7 (475)	20.6 (523)
Mounting method		Suspended	
Cutting width	in. (mm)	54 (1372)	60 (1524)
Cutting height	in. (mm)	1.0 to 4.0 (25 to 102)	
Adjustment of cutting height		Dial	
Weight (approx.)	lbs.(kg)	300 (136)	322 (146)