

M Series

Specifications

M5660SU



Model	M5660SUH		M5660SUHD	
	2WD		4WD	
Engine	V2403-CR-TE4			
Type (Make: KUBOTA)	4 cylinder in-line, Common Rail Sytem, direct injection			
Rated Engine HP (97/68/EC)	HP (kW)	57.9 (43.2) @2600 rpm		
Engine net power (SAE J1349)	HP (kW)	56 (41.8) @2600 rpm		
PTO power (at rated engine RPM)	HP (kW)	50 (37.3)		
No. of cylinders/Aspiration	4 / Turbocharged			
Total displacement	cu. in. (cc)	148.5 (2434)		
Fuel tank capacity	US gal. (ℓ)	17.7 (67)		
Air cleaner	Dry, dual element			
Alternator	Amp	45		
Transmission				
No. of speeds	8F/8R			
Main gear shift (4 speeds)	Fully synchronized			
Shuttle	Hydraulic shuttle			
Main clutch	Multiple wet disk			
Brake	Mechanical wet disc			
Differential lock	Rear standard (mechanical)			
PTO				
PTO type	Live-independent, hydraulic PTO with PTO brake, multi-plate wet clutch			
Speed	@540 rpm (540/540E opt)			
Hydraulic				
Pump capacity (main)	gpm (ℓ/min)	10.6 (40.2)		
3-point hitch	Category I & II			
Control system	Position			
Lift capacity at 24 in. behind lift point	lbs. (kg)	3307 (1500)		
No. of remote valves	1 (2nd, 3rd & flow control valve optional)			
Tires				
Standard	2WD	Front/Rear	6.5-16 / 14.9-28	
	4WD	Front/Rear	8.3-24 / 14.9-28	
Traveling speeds (w/std. 4WD Ag. tires)				
No. of speeds (at rated engine speed)			Forward	Reverse
First	Fifth	mph (km/h)	1.6 (2.6)	6.1 (9.7)
Second	Sixth		1.6 (2.6)	6.2 (9.9)
Third	Seventh		2.2 (3.6)	8.5 (13.7)
Fourth	Eighth		2.3 (3.7)	8.7 (14.0)
			3.1 (5.1)	12.0 (19.2)
			3.2 (5.2)	12.2 (19.6)
			4.8 (7.7)	18.2 (29.3)
			4.9 (7.8)	18.6 (29.9)
Other features				
4WD drive system (4WD model)	Bevel gear type with 55 degree turning angle			
Steering	Hydrostatic power steering			
Hood type / Pedal type	Full open, slanted, steel / Hanging			
Deck type	Semi-flat			
Dimensions				
Overall length	in. (mm)	138.7 (3525)		136 (3455)
Overall height (w/Foldable ROPS)	in. (mm)	95.3 (2420)		
Overall width (Minimum)	in. (mm)	73.2 (1860)		
Wheelbase	in. (mm)	82 (2085)		80.7 (2050)
Min. ground clearance	in. (mm)	16.3 (415)		
Tread width	Front	in. (mm)	55.9, 71.7 (1420, 1820)	
	Rear	in. (mm)	52.0, 67.7 (1320, 1720)	
Turning radius (w/o brake)	ft. (m)	10.8 (3.6)		12.8 (3.9)
Weight (with ROPS)	lbs. (kg)	4189 (1900)		4387 (1990)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.