

Z300 Series

Specifications

ZG327 - ZG332 - ZD323 - ZD326 - ZD331



Specifications

Model		ZG327		ZG332		ZD323		
		ZG327PA-60	ZG327RPA-60R	ZG332P-60	ZG332LP-72	ZD323-60		
Engine	Model	Kubota KGZ770-E2-MA1		Kubota KG770-E2-MA1		Kubota WG972-G-E3-ZG-1		
	Type	Gasoline, air-cooled V-Twin with heavy-duty canister air filter		Gasoline, liquid-cooled (3 cyl.)		Diesel, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	27HP@3600 rpm		32.5HP@3600rpm		23HP@3200rpm		
	Total displacement	cu.in. (cc)	46.9 (768)		58.7 (962)		54.8 (898)	
	Starting system	Key switch					Key switch - super glow	
Dimensions	Overall length	in. (mm)	87.8 (2230)		91.7 (2329)	95.0 (2414)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	63.1 (1604)	75.2 (1911)	87.6 (2224)	72.8 (1850)
		(w/o mower)	in. (mm)	57.5 (1460)				
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)				
(w/ ROPS folded)		in. (mm)	61.2 (1555)		64.8 (1645)		61.2 (1555)	
Wheel base		in. (mm)	55.5 (1410)		52.5 (1333)	58.9 (1495)	55.5 (1410)	
Tread	Front	in. (mm)	38.4 (975)			42.1 (1070)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)					
Tire size	Front		15 x 6.0-6 Non-flat			15 x 6.0-6 Pneumatic		
	Rear		26 x 12.0-12					
Weight (w/ mower)		lbs. (kg)	1565 (710)		1651 (749)	1763 (800)	1645 (746)	
Transmission system	2-HST w/ Gear reduction							
Speed control	2-hand lever							
Travel speed range	Forward	mph (km/h)	0-10.6 (0-17.0)			0-9.3 (0-15.0)		
	Reverse	mph (km/h)	0-5.3 (0-8.5)			0-5.2 (0-8.3)		
Brake type	Wet multi disks, foot applied, released							
PTO	Type	Shaft drive						
	Clutch type	Hydraulic independent PTO clutch with wet multi disks						
	PTO brake	Wet single disk						
Mower deck	Model		RCK60P-327Z	RCK60P-331Z	RCK60P-327Z	RCK72P-332Z	RCK60P-331Z	
	Mower lift system	Hydraulic						
	Mower deck type	Pro commercial - Fabricated deck						
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)	6.5 (165)			
	Belt type	Multi-Belt						
	Deck steel thickness	in. (mm)	0.17 (4.2)					
	Anti-scalp roller		Rigid	Swivel	Rigid	Swivel		
	Cutting width of mower		60 in.			72 in.	60 in.	
	Number of blades	3 blades						
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments						
	Mounting system of mower	Quick joint, parallel linkage						
	Blade tip speed (max.)		18100 FPM	17100 FPM	18100 FPM	18200 FPM	18100 FPM	
	Engine stop system	Key stop						
Fuel tank capacity		gals. (ltrs.)	12.7 (48)			12.9 (49)		
Battery	U1L10 (12V, RC: 22 min., CCA: 300, CA: 365)			51R (12V, RC: 70 min., CCA: 475A)				
Alternator capacity	13.4 Amps at 12 Volts			14 Amps at 14 Volts				
Water temperature indicator	-			Standard				
Hour meter	Standard							
Fuel gauge	Electric							

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

Z300 Series

Specifications

ZG327 - ZG332 - ZD323 - ZD326 - ZD331



Specifications

Model		ZD326		
		ZD326S-60	ZD326P-60	ZD326RP-60R
Engine	Model	Kubota D1005-E3-ZD-2		
	Type	Diesel, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	26HP @ 3200rpm		
	Total displacement	cu.in. (cc)	61.1 (1001)	
	Starting system	Key switch - super glow		
Dimensions	Overall length	in. (mm)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)
		(w/o mower)	in. (mm)	57.5 (1460)
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)
		(w/ ROPS folded)	in. (mm)	61.2 (1555)
Wheel base		in. (mm)	55.5 (1410)	
Tread	Front	in. (mm)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)	
Tire size	Front		15 × 6.0-6 Pneumatic	15 × 6.0-6 Non-Flat
	Rear		26 × 12.0-12	
Weight (w/ mower)	lbs. (kg)	1667 (756)	1700 (771)	1667 (756)
Transmission system		2-HST w/ Gear reduction		
Speed control		2-hand lever		
Travel speed range	Forward	mph (km/h)	0-9.3 (0-15.0)	0-10.6 (0-17.0)
	Reverse	mph (km/h)	0-5.2 (0-8.3)	0-5.3 (0-8.5)
Brake type		Wet multi disks, foot applied, released		
PTO	Type	Shaft drive		
	Clutch type	Hydraulic independent PTO clutch with wet multi disks		
	PTO brake	Wet single disk		
Mower deck	Model		RCK60P-331Z	RCK60R-331Z
	Mower lift system	Hydraulic		
	Mower deck type	Pro commercial—Fabricated deck		
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)
	Belt type	Multi-Belt		
	Deck steel thickness	in. (mm)	0.17 (4.2)	
	Anti-scalp roller	Swivel		
	Cutting width of mower	60 in.		
	Number of blades	3 blades		
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower	Quick joint, parallel linkage		
	Blade tip speed (max.)		18100 FPM	17100 FPM
Engine stop system		Key stop		
Fuel tank capacity	gals. (ltrs.)	12.9 (49)		
Battery		51R (12V, RC: 70 min., CCA: 475A)		
Alternator capacity		14 Volts at 14 Amps		
Water temperature indicator		Standard		
Hour meter		Standard		
Fuel gauge		Electric		

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

Z300 Series

Specifications

ZG327 - ZG332 - ZD323 - ZD326 - ZD331



Specifications

Model		ZD331				
		ZD331P-60	ZD331LP-72	ZD331RP-60R		
Engine	Model	Kubota D1305-E3-ZD				
	Type	Diesel, liquid-cooled (3 cyl.)				
	Max. horsepower (Gross)	31HP @ 3000rpm				
	Total displacement	77.0 (1261)				
	Starting system	Key switch - super glow				
Dimensions	Overall length	in. (mm)	87.4 (2220)	91.9 (2335)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	87.6 (2224)	63.1 (1604)
		(w/o mower)	in. (mm)		57.5 (1460)	
	Overall height	(w/ ROPS upright)	in. (mm)		75.4 (1915)	
(w/ ROPS folded)		in. (mm)		61.2 (1555)		
Wheel base		in. (mm)	55.5 (1410)	59.8 (1520)	55.5 (1410)	
Tread	Front	in. (mm)	38.4 (975)	42.1 (1070)	38.4 (975)	
	Rear	in. (mm)		45.3 (1150)		
Tire size	Front		15 x 6.0-6 Non-Flat			
	Rear		26 x 12.0-12			
Weight (w/ mower)		lbs. (kg)	1715 (778)	1770 (803)	1681 (763)	
Transmission system			2-HST w/ Gear reduction			
Speed control			2-hand lever			
Travel speed range	Forward	mph (km/h)	0-10.6 (0-17.0)			
	Reverse	mph (km/h)	0-5.3 (0-8.5)			
Brake type			Wet multi disks, foot applied, released			
PTO	Type		Shaft drive			
	Clutch type		Hydraulic independent PTO clutch with wet multi disks			
	PTO brake		Wet single disk			
Mower deck	Model		RCK60P-331Z	RCK72P-331Z	RCK60R-331Z	
	Mower lift system		Hydraulic			
	Mower deck type		Pro commercial—Fabricated deck			
	Deck depth	in. (mm)	6.5 (165)		5.5 (140)	
	Belt type		Multi-Belt			
	Deck steel thickness	in. (mm)	0.17 (4.2)			
	Anti-scalp roller		Swivel			
	Cutting width of mower		60 in.	72 in.	60 in.	
	Number of blades		3 blades			
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments			
	Mounting system of mower		Quick joint, parallel linkage			
	Blade tip speed (max.)		18200 FPM		17100 FPM	
Engine stop system			Key stop			
Fuel tank capacity		gals. (ltrs.)	12.9 (49)			
Battery			51R (12V, RC: 70 min., CCA: 475A)			
Alternator capacity			14 Volts at 14 Amps			
Water temperature indicator			Standard			
Hour meter			Standard			
Fuel gauge			Electric			

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

Z300 Series

Specifications

ZG327 - ZG332 - ZD323 - ZD326 - ZD331



Specifications

Model		ZP330P-60	ZP330LP-72	
Engine	Model	Kubota WG972-GL-E3-ZG-1		
	Type	LPG, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	31 HP@3600 rpm		
	Total displacement	58.7 cu.in. (962 cc)		
	Starting system	Key switch		
Dimensions	Overall length	91.7 in. (2329 mm)	95 in. (2414 mm)	
	Overall width	(w/ mower)	75.2 in. (1911 mm)	87.6 in. (2224 mm)
		(w/o mower)	66.1 in. (1679 mm)	
	Overall height	(w/ ROPS upright)	75.4 in. (1915 mm)	
(w/ ROPS folded)		64.8 in. (1645 mm)		
Wheel base		55.5 in. (1410 mm)	58.8 in. (1495 mm)	
Tread	Front	38.4 in. (975 mm)	42.1 in. (1070 mm)	
	Rear	45.3 in. (1150 mm)		
Tire size	Front	15 x 6.0-6 flat free		
	Rear	26 x 12.0-12		
Weight (w/ mower) (with LPG fuel tank)		1876 lbs. (851 kg)	1940 lbs. (880 kg)	
Transmission system		2-HST w/ Gear		
Speed control		2-hand lever		
Travel speed range	Forward	0-10.6 mph (0-17.0 km/h)		
	Reverse	0-5.3 mph (0-8.5 km/h)		
Brake type		Wet multi disks, foot applied, released		
PTO	Type	Shaft drive		
	Clutch type	Hydraulic independent PTO clutch with wet multi disks		
	PTO brake	Wet single disk		
Mower deck	Model	RCK60P-327Z	RCK72P-332Z	
	Mower lift system	Hydraulic		
	Mower deck type	Pro commercial— Fabricated deck		
	Deck depth	6.5 in. (165 mm)		
	Belt type	Multi-Belt		
	Deck steel thickness	0.17 in. (4.2 mm)		
	Anti-scalp roller	Rigid		
	Cutting width of mower	60 in.	72 in.	
	Number of blades	3 blades		
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower	Quick joint, parallel linkage		
	Blade tip speed (max.)	18500 FPM		
	Engine stop system		Key stop	
Fuel tank capacity		33.5 lbs x 2 (15.2 x 2 kg)		
Battery		51R (12 V, RC: 70 min., CCA: 475)		
Alternator capacity		14 Amps@14 Volts		

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.