



COMPETITIVE COMPARISON

MODEL	Kubota ZD321	Kubota ZD323	Kubota ZD326	John Deere 997 Diesel	Exmark Lazer Z XS	Scag Turf Tiger	Kubota ZD331	John Deere Z830A	Scag Turf Tiger	Exmark Next Lazer Z	Kubota ZG327-60		
Engine	Manufacturer	Kubota	Kubota	Kubota	Yanmar	Kubota	Kubota / CAT	Kubota	Kawasaki	Kohler	Kohler	Kubota	
	Model No.	D782	D902	D1005	3TNV82A	D902	--	D1305	---	--	--	KGZ770	
	Horsepower (gross)	21 @ 3200rpm	23 @ 3200 rpm	26 @ 3200 rpm	31 @ 3000 rpm	25 @ 3850 rpm	25 / 28	31 @ 3000 rpm	27 HP	27	23 HP / 27 HP	27 HP	
	Displacement	47.5 cu in	54.8 cu in	61.1 cu in	81 cu in	54.8 cu in	54.8 / 69 cu in	77 cu in	852 cc	--	--	768 cc	
	Cylinders	3	3	3	3	3	3	3	Two	Two	Two	Two	
	Oil Filter	Full flow, replaceable	Full flow, replaceable	Full flow, replaceable	Full flow, replaceable	Spin on	Spin on	Full flow, replaceable	Full flow, replaceable	Yes	Yes	Full flow, replaceable	
	Lubrication	Full pressure	Full pressure	Full pressure	Full pressure	Full pressure	Full pressure	Full pressure	Full pressure	--	Pressure	Full pressure	
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Air	Air	Air	Air	
	Air Cleaner	Heavy duty canister style	Heavy duty canister style	Heavy duty canister style	Heavy duty canister style	Canister Type	Canister Type	Heavy duty canister style	Heavy duty canister style	Canister Type	Canister	Heavy duty canister style	
Pre-Cleaner	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Fuel System	Fuel Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Gas	Gas	Gas	Gas		
	Fuel Tank Capacity	12.9 Gal	12.9 Gal	12.9 Gal	12 Gal	15 Gal	11 Gal	12.9 Gal	11.5 gallons	10 Gal	12 gallons	12.9 gallons	
Electrical System	Charge System	14 amp	14 amp	14 amp	40 amp	40 amp	40 amp	14 amp	20 amp	40 amp	--	13.5 amp	
	Battery Voltage	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt	
	Cold Cranking Amp	450	450	450	490	--	300	450	340	300	--	300	
	Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Yes	Standard	
	Operator Presence Starting System	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Drive Train	Transmission	HST, Kubota	HST, Kubota	HST, Kubota	Parker Ross, Wheel Motors	Parker Ross, Wheel Motors	Parker Ross, Wheel Motors	HST, Kubota	Parker Ross, Wheel Motors	Parker Ross, Wheel Motors	12 cc, Parker	HST, Kubota	
	Travel Speed	Forward	0-9.3 mph	0-9.3 mph	0-9.3 / 0-10.6 mph	0-11.5 mph	0-12 mph	0-11 mph	0-10.6 mph	0-12 mph	0-11 mph	0-11.5 mph	0-10.6 mph
		Reverse	0-5.2 mph	0-5.2 mph	0-5.2 / 0-5.3 mph	0-5 mph	0-8 mph	0-5 mph	0-5.3 mph	0-5 mph	0-5 mph	0-7 mph	0-5.3 mph
	Speed and Direction Control	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin levers	Twin Levers	Twin levers
	Hydraulic Capacity	19 quarts	19 quarts	19 quarts	12.8 quarts	--	--	19 quarts	2.9 quarts	--	1.7 quarts	19 quarts	
Filter	Yes	Yes	Yes	Yes	---	---	Yes	Spin-on type	Spin-on type	Spin-on type	Spin-on type		
Brakes	Park Brake	Wet Multi Disc	Wet Multi Disc	Wet Multi Disc	Disc	Band	--	Wet Multi Disc	Drum	--	Disc & Caliper	Internal Expanding Shoe	
	Park Brake Actuation	Foot Pedal	Foot Pedal	Foot Pedal	Hand Lever	Hand Lever	Hand Lever	Foot Pedal	Foot Pedal	Hand Lever	Hand Lever	Foot Pedal	
PTO	Type	Hydraulic Wet Disc	Hydraulic Wet Disc	Hydraulic Wet Disc	Hydraulic	Electric	Electric	Hydraulic Wet Disc	Electro-Magnetic	Electric	Electric	Wet Disc-type	
	Drive	Full Shaft	Full Shaft	Full Shaft	V-belt	Mule Belt	Belt to Shaft	Full Shaft	V-belt	Belt to Shaft	Belt	Shaft	
Mower Decks	Available Widths	54" / 60"	60"	60"	60" / 72"	60" / 72"	61" / 72"	60" / 72"	60"	60" / 72"	60"	60"	
	Deck construction	Fabricated-Pro Commercial	Fabricated-Pro Commercial	Fabricated-Pro Commercial	Stamped	Fabricated	Fabricated	Fabricated-Pro Commercial	Stamped	Fabricated	Fabricated	Kubota Pro Commercial	
	Deck thickness	.17 in. / .18 in.	.17 in. / .18 in.	.17 in. / .18 in.	.177 in.	--	--	.17 in. / .18 in.	7 gauge	7 gauge	7 gauge	7 gauge	
	Height-of-Cut Range	1 - 5 in.	1 - 5 in.	1 - 5 in.	1.5 - 5 in.	1 - 5 in.	1 - 6 in.	1 - 5 in.	1.5 - 5 in.	1 - 6 in.	1 - 5.5 in.	1 - 5 in.	
	Increments	0.25 in.	0.25 in.	0.25 in.	0.25 in.	0.25 in.	0.25 in.	0.25 in.	0.25 in.	.25"	0.25 in.	0.25 in.	
Blades	Tip Speed	17300	18100	18100	18000	18,000 / 18,500	--	18,100 / 18,200	18000	--	18500	18100	
Wheels	Drive Tires	26 x 10.5-12 / 26x12-12	26x12-12	26x12-12	26x12-12	26x12-12	24x12-12	26x12-12	24 x 12-12	24 x 12-12	24 x 12-12	26 x 12-12	
	Caster Wheel Type	pneumatic	pneumatic	pneumatic/ flat-free	flat-free	flat-free	flat-free	flat-free	flat-free	flat-free	flat-free	flat-free	
	Caster Wheel Size	15x6-6	15x6-6	15x6-6	15x6-6	13x6.5-6	13x6.5-6	15x6-6	13x6.5-6	13x6.5-6	13 x 5-6	15x6-6	
Dimensions	Length	86"	87.4"	87.4"	96"	84.5" / 88.7"	87.5" / 90"	87.4" / 91.9"	84"	87.5" / 90"	83.1"	---	
	Width	67.1" / 72.8"	72.8"	75.2"	74" / 86"	72.8" / 85.8"	73.5" / 80"	75.2" / 85.5"	73"	73.5" / 80"	72.7" / 87.5"	---	
	Height	75.4"	75.4"	75.4"	85"	72.7"	67.5"	75.4"	73"	67.5"	70.5"	70"	
	Weight	1517 / 1645	1645	1667 / 1700	1774 / 1815	1610 / 1710	1700 / 1750	1773 / 1812	1360	1700 / 1750	1116	1560	

N/A = Not Available N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.