

Husqvarna Bar & Chain Applications

GUIDE BARS

1	BAR DESCRIPTION	2	MOUNT	3	PITCH	4	GAUGE	5	DRIVE LINK
---	-----------------	---	-------	---	-------	---	-------	---	------------

1 DESCRIPTION

HLI	=	Intenz, Adjustable Guide Bar
HL	=	Laminated, Sprocket Nose Guide Bar
HLN	=	Laminated, Narrow Sprocket Nose Bar (Pixel or Micro-Lite)
FT	=	FT = FARM Tough - Bar for Rancher models, 359 or 460, Laminated
TLR	=	TechLite, Guide Bar 20% Lighter Than Traditional Bars
HT	=	Power Match, Replaceable Tip, Sprocket Nose Guide Bar
HTR	=	Power Match, Replaceable Tip, Reduced Weight, Sprocket Nose Guide Bar
HA	=	Armor Tip, Solid Nose Guide Bar
EMAB	=	Professional Quality Laminated Bars, Sprocket Nose Bar (EMAB = Electrolux Motors AB)

2 MOUNT

1	=	SMALL MOUNT - AO41 136, 137, 141, 142, 235 and 240
2	=	SMALL MOUNT - K095 55 Rancher, 242XP, 254XP, 257, 261, 262XP, 334T, 335XPT, 336, 338XPT, 339XP, 340, 345, 350, 353, 346XP, 362XP, 357XP, 359, 435, 440, 445, 450, 455 Rancher, 460, 460 Rancher
3	=	LARGE MOUNT - D009 61, 266XP, 268, 272XP, 365, 371XP, 372XP, 281XP, 288XP, 385XP, 390XP, 394XP, 395XP, 3120XP, 570, 575XP, 576XP

NOTE:

Compact 23 takes an Oregon A041 mount. Models 36 & 41 can also use this mount.

3 PITCH

5	=	.325"
8	=	3/8"
4	=	.404"

4 GAUGE

0	=	.050"
8	=	.058"
3	=	.063"
6	=	.043"

Bar Reference I.D.

HT	3	8	0-	72
1	2	3	4	5

5 DRIVE LINK COUNT

Number of Drive Links in the Chain Loop

1	BAR DESCRIPTION	2	MOUNT	3	PITCH	4	GAUGE	5	DRIVE LINK
---	-----------------	---	-------	---	-------	---	-------	---	------------

Example: HL258-66

Husqvarna Branded, Oregon Laminated Bar, Small Husqvarna Mount, 325" Pitch, .058" Gauge, 66 Drive Links

Example: HT380-72

Husqvarna Branded, Oregon Power Match Bar, Large Husqvarna Mount, 3/8" Pitch, .050" Gauge, 72 Drive Links

SAW CHAIN

Models 36, 136, 40, 41, 141, 42, 45, 51 and 55, 235, 236, 240 are recommended with Low Kickback Chain (Green Label) to comply with ANSI B 175.1-2000 Standards. Professional Chains (Yellow Label) meets the kickback performance requirements of CSA Standard Z62.3 when used on specific chainsaws models. For further details, see you chainsaw operators manual. It may not meet the requirements of CSA Standard Z62.3 when used on other saws.

Models 42, 246, 242XP, 257, 351, 353, 357XP, 359, 346XP, 435, 440, 445, 450 455, 460, 543XP, 545 and 550XP are recommended with either Low Kickback (Green Label) or Professional Chain (Yellow Label) depending on the User's Preference.

Models above 3.8 cubic inches are recommended with Professional Chain (Yellow Label). Includes 261, 262 XP, 266 XP, 268, 272 XP, 281 XP, 288 XP, 362 XP, 365, 371 XP, 372 XP, 385 XP, 390 XP, 394 XP, 395 XP, 3120 XP, 575 XP, 576 XP, 555 and 562 XP.